

Catellani & Smith

Collection: Eco-Logic Light - 2008-2012

WA WA Parete/Soffitto

Wall or ceiling lamp



Materials

nickel-plated metal base and structure, nickel-plated copper sticks, nickel flex, glass lenses Ø 32 mm.

LED

6x1W,

Neutral White (4100 °K): 660 lm,

Warm White (2800 °K): 540 lm.

8x1W,

Neutral White (4100 °K): 880 lm,

Warm White (2800 °K): 720 lm.

10x1W,

Neutral White (4100 °K): 1100 lm,

Warm White (2800 °K): 900 lm.

Power Supply

6 LED: voltage 230V, rated output 6W 350 mA.

Driver included, dimmable (cod. ED1).

8/10 LED: voltage 110V-240V, rated output 8W or 10W 350 mA. Driver included, dimmable (cod. ED2).

Dimensions

ledge 28 cm.

6 LED: base (B4) Ø 9x5,5 cm, bar length 160 cm.

8 LED: base (B3) 15x8x3,5 cm, bar length 184 cm.

10 LED: base (B3) 15x8x3,5 cm, bar length 230 cm.

Order code

6 LED

ECWWP601 neutral white

ECWWP602 warm white

8 LED

ECWWP801 neutral white

ECWWP802 warm white

10LED

ECWWP1001 neutral white

ECWWP1002 warm white

JACK Connection System.
Registered Community Model.